Weatherproof central control hub for WaveLinx wireless lighting control systems in outdoor environments. Integrates a WaveLinx Area Controller, 7-inch touchscreen user interface, and 8-port PoE switch in a NEMA 4X rated enclosure — pre-wired and fully assembled for rapid outdoor deployment.

KEY FEATURES

✓ Integrated WaveLinx Area Controller for centralized outdoor lighting management

✓ 7-inch touchscreen with edge-to-edge glass and high-resolution display

✓ Raise, lower, and adjust light levels for entire areas or individual zones

✓ Built-in scheduling, manual control, and system status monitoring

✓ 8-port PoE switch for network and device connectivity

✓ Configurable via WaveLinx Mobile application

✓ NEMA 4X rated enclosure — weatherproof, UV and corrosion resistant

✓ Pre-wired and fully assembled for rapid deployment

✓ Powered by 120VAC circuit

SPECIFICATIONS

Enclosure Rating	NEMA 1/3R/4/4X/12	**Network**	8-port PoE switch
Enclosure Dimensions	16 in H x 14 in W x 8 in D	**Power Input**	120VAC
Enclosure Material	UV and corrosion resistant	**Controller**	WaveLinx Area Controller (WAC)
Touchscreen	7-inch, edge-to-edge glass, high resolution	**Configuration**	WaveLinx Mobile application

ORDERING INFORMATION

Part Number	Description
CUST-PNL-WAC-TSE-08POE-NEMA4X	Outdoor WAC Control Hub, 8-port PoE, NEMA 4X, 120VAC

UL Listed   NEMA 4X